


RW 174 211100		WATER WELL RECORD		Form WWC-5	KSA 82a-1212
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE 1/4 SW 1/4 NE 1/4	14	T 28 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city?					
BOEING S OF SE CORNER OF ASSEMBLY SUPPORT BUILDING					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:					
WICHITA, KS 67211-7130					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 39 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 16.76 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16.76 ft. below land surface measured on mo/day/yr 3-27-94			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 12 in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well RECOVERY			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded SCREWED			
2 PVC 4 ABS		Threaded			
Blank casing diameter 5 in. to ft., Dia 6.5 in. to ft., Dia		Casing height above land surface 36 in., weight 6.5 lbs./ft. Wall thickness or gauge No. SDR-21			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 17 ft. to 39 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 16 ft. to 39 ft., From ft. to ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other			
Grout intervals: From 16 ft. to 2 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage NA		NA			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage NA		NA			
Direction from well? NA		How many feet? NA			
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0 1.0 TOPSOIL, CLAY, SILT					
1.0 12.5 CLAY, SILT					
12.5 18.0 CLAY, SILT					
18.0 30.0 CLAY, SILT, SAND					
30.0 32.5 SAND					
32.5 38.0 CLAY					
38.0 40.0 SHALE					
NOTE: ALLISON RAWIN CONTACTED DON TAYLOR ABOUT FORMS BEING TURNED IN LATE ON 4-27-94 @ 9:00 A.M.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-27-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 5-17-94 under the business name of GSI by (signature) M. J. Simpson					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					