


RW 179 2111100

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: <u>SEDGWICK</u>		Fraction <u>SE 1/4 SW 1/4 NE 1/4</u>	Section Number <u>14</u>	Township Number T <u>28</u> S	Range Number R <u>1</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>BOXING S OF IPB3 BUILDING</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>57</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>33</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>24.93</u> ft. below land surface measured on mo/day/yr <u>3-27-94</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter <u>12</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>RECOVERY</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter <u>5</u> in. to ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>36</u> in. weight <u>6.5</u> lbs./ft. Wall thickness or gauge No. <u>SOR-21</u>		CASING JOINTS: Glued <u>Clamped</u> Welded <u>SCREWED</u> Threaded 5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>17</u> ft. to <u>57</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>16</u> ft. to <u>57</u> ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>16</u> ft. to ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>NA</u> How many feet? <u>NA</u>			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 18.0 CLAY, SILT					
18.0 41.0 CLAY, SILT, SAND					
41.0 46.0 CLAY, SAND					
46.0 50.0 SANDSTONE					
50.0 56.0 CLAY					
56.0 57.0 SHALE					
NOTE: ALLISON IRWIN CONTACTED DON TAYLOR ABOUT FORMS BEING TURNED IN LATE ON 4-27-94 @ 9:00 A.M.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-27-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>5-17-94</u> under the business name of <u>GSI</u> by (signature) <u>Mick Simpson</u>					