

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: JEDG WICK		SW 1/4 SE 1/4 SW 1/4	14	T 28 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 3600 E. 47TH ST WICHITA KS					
2 WATER WELL OWNER: KIRTLGYS TIRE + AUTO WICHITA					
RR#, St. Address, Box # POOR BOY TIRE - 3600 E 47TH ST WICHITA KS. 67210					
City, State, ZIP Code					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 22.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 16.8 ft. 2. — ft. 3. — ft.			
		WELL'S STATIC WATER LEVEL 12.67 ft. below land surface measured on mo/day/yr 12-21-93			
		Pump test data: Well water was — ft. after — hours pumping — gpm			
		Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm			
		Bore Hole Diameter 7.25 in. to 22.5 ft., and — in. to — ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —					
Water Well Disinfected? Yes — No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped — 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded — 7 Fiberglass Threaded X					
Blank casing diameter 2 in. to 12 ft., Dia — in. to — ft., Dia — in. to — ft.					
Casing height above land surface FLUSH MOUNT weight SC4 40 lbs./ft. Wall thickness or gauge No. —					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) — 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) —					
SCREEN-PERFORATED INTERVALS: From 12 ft. to 22 ft., From — ft. to — ft.					
SAUD GRAVEL PACK INTERVALS: From 11 ft. to 22.5 ft., From — ft. to — ft.					
From — ft. to — ft., From — ft. to — ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other —					
Grout Intervals: From 2 ft. to 9 ft., From 3 ft. to 9 ft., From 11 ft. to — ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage * CONTAMINATED SITE					
Direction from well? — How many feet? —					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
6.1	3	SOIL			* OTHERS UP GRADE
3	7	CLAY SILT			WATER FLOW - DUMP -
7	10	SILTY CLAY			AND BOEING -
10	15	CLAY			
15	16.8	SILTY SAND			
16.8	22.5	SAND			
20	22.5				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-15-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 12-22-93 under the business name of EBBERTS DRILLING by (signature) <i>Steve Ebberts</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					