

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number																																										
County: Sedgwick		SW ¼ SW ¼ NE ¼	15	T 28 S	R 1 EW																																										
Distance and direction from nearest town or city street address of well if located within city? 700' West and 2300' South of Kansas Turnpike and MacArthur Road, Wichita, KS 52915087 MW-5																																															
2) WATER WELL OWNER: Boeing Commercial Airplane Group RR#, St. Address, Box #: P.O. Box 7730, M/S K11-65 City, State, ZIP Code: Wichita, KS 67277-7730 Board of Agriculture, Division of Water Resources Application Number:																																															
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4) DEPTH OF COMPLETED WELL: 23.5 ft. ELEVATION: Approx. Surf. Elev.: 1,268 ft. Depth(s) Groundwater Encountered 1. 11.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11.5 ft. below land surface measured on mo/day/yr 07/18/91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 23.5 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X																																														
5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 8.5 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 8.5 ft. to 23.5 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 7.5 ft. to 23.5 ft., From ft. to ft.																																															
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 6 ft., From 6 ft. to 7.5 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? North How many feet? 2,450 <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>2.0</td> <td>Silty Lean Clay, Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2.0</td> <td>6.5</td> <td>Sand, Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6.5</td> <td>9.0</td> <td>Clayey Sand, Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>9.0</td> <td>18.5</td> <td>Sand, Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>18.5</td> <td>22.0</td> <td>Fat Clay, Olive-Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>22.0</td> <td>23.0</td> <td>Highly Weathered Shale, Gray</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	2.0	Silty Lean Clay, Brown				2.0	6.5	Sand, Brown				6.5	9.0	Clayey Sand, Brown				9.0	18.5	Sand, Brown				18.5	22.0	Fat Clay, Olive-Gray				22.0	23.0	Highly Weathered Shale, Gray			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																										
0	2.0	Silty Lean Clay, Brown																																													
2.0	6.5	Sand, Brown																																													
6.5	9.0	Clayey Sand, Brown																																													
9.0	18.5	Sand, Brown																																													
18.5	22.0	Fat Clay, Olive-Gray																																													
22.0	23.0	Highly Weathered Shale, Gray																																													
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/16/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 08/20/91 under the business name of Terracon Consultants, inc. by (signature)																																															

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.