


LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NW 1/4 NE 1/4 NE 1/4	15	T 28 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city?					
610' S. of 2800 E. MacArthur Road, Wichita, KS			52895023		TMW-1
WATER WELL OWNER: Boeing Military Airplanes					
RR#, St. Address, Box # : P. O. Box 7730 M/S K06-00			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, KS 67277-7730			Application Number:		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 28 ft. ELEVATION: Approx. Surface Elev: 1270.5			
<div style="text-align: center;">N W E S</div> 		Depth(s) Groundwater Encountered 1. 16 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 9.9 ft. below land surface measured on mo/day/yr 06/22/89			
		Pump test data: Well water ft. after hours pumping gpm			
		Est. Yield 1 gpm: Well water ft. after hours pumping gpm			
Bore Hole Diameter 12 in. to 28 ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)			
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 5 in. to 10.5 ft., Dia in. to ft.					
Casing height above land surface 50 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 10.5 ft. to 28 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 28 ft., From ft. to ft.					
5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 8 ft., From 8 ft. to 10 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage Landfill					
Direction from well? - How many feet? 0'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	Fill: Sand with trash			
10	14	Fill: Fat Clay			
14	19	Fill: Clayey Sand with debris			
19	21	Fill: Sludge			
21	28	Highly Weathered Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/24/89 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10/19/89					
Under the business name of Terracon Consultants, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4