

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SW 1/4 NE 1/4 NE 1/4	15	T 28 S	R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 1,320' South of 2800 East MacArthur Road, Wichita, KS 52895023/52905043 TMW-2					
2 WATER WELL OWNER:		(Boeing Landfill)			
RR#, St. Address, Box # : P. O Box 7730 M/S K11-65		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Wichita, KS 67277-7730		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 21 ft. ELEVATION: Approx. Surface Elev: 1265.0			
<div style="text-align: center;"><p>1 Mile</p></div>		Depth(s) Groundwater Encountered 1. 6 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 6.1 ft. below land surface measured on mo/day/yr 06/23/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <1 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 12 in. to ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel		5 Wrought iron	8 Concrete tile	Welded	
3 RMP (SR)		6 Asbestos-Cement	9 Other (specify below)	Threaded	
2 PVC		7 Fiberglass			
4 ABS					
Blank casing diameter 5 in. to ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 3 Below in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Sand			
Grout Intervals: From 0 ft. to 6 ft., From 6 ft. to 21 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	Landfill
Direction from well?		How many feet? 0			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			21.0	6.0	Sand
			6.0	0.0	Bentonite-Cement Grout
					Sand was placed in the casing to the approximate phreatic surface. Well was plugged with bentonite-cement grout. Area to be filled to a level more than 3" above top of casing.
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/07/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 5-30-90 under the business name of Terracon Consultants, Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					