


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 17	Township Number T 28 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 47th & S BROADWAY WICHITA KS MW2					
2 WATER WELL OWNER: COASTAL RR#, St. Address, Box #: 305 N MACARTHUR City, State, ZIP Code: OKC OK			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 19 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 14 ft. 2. 19 ft. 3. 19 ft. WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr Pump test data: Well water was 8 ft. after 19 hours pumping 19 gpm Est. Yield 8 gpm: Well water was 19 ft. after 19 hours pumping 19 gpm Bore Hole Diameter 8 in. to 19 ft., and 19 in. to 19 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes.....No..... ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes.....No..... ☒			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued.....Clamped..... 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded..... Blank casing diameter 2 in. to 9 ft., Dia. 9 in. to 19 ft., Dia. 19 in. to 19 ft. Casing height above land surface 9 in., weight 9 lbs./ft. Wall thickness or gauge No. 9 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)..... SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 9 ft. to 19 ft., From 9 ft. to 19 ft., From 9 ft. to 19 ft. GRAVEL PACK INTERVALS: From 8 ft. to 19 ft., From 8 ft. to 19 ft., From 8 ft. to 19 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other..... Grout Intervals: From 0 ft. to 8 ft., From 8 ft. to 19 ft., From 19 ft. to 19 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 <u>Livestock pens</u> 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 <u>Fuel storage</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? WITHIN STATION How many feet? WITHIN STATION					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		6		SILTY CLAY	
6		TO		SAND	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/2/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 107 This Water Well Record was completed on (mo/day/yr) 7/10/92 under the business name of LAYNE-WESTERN CO by (signature) [Signature]					