

1) LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 NE 1/4 SE 1/4		Section Number 19		Township Number T 28 S		Range Number R 1 EW	
Distance and direction from nearest town or city street address of well if located within city? 475 Feet West and 1,820 Feet North of 55th Street South & Seneca, Wichita, KS						01938017 MW-3			
2) WATER WELL OWNER: City of Wichita, Public Works Department RR#, St. Address, Box #: 455 North Main Street City, State, ZIP Code: Wichita, KS 67202						Board of Agriculture, Division of Water Resources Application Number:			
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 15 ft.		ELEVATION: Approx. Surface Elev.: 1270.2					
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.		WELL'S STATIC WATER LEVEL 7.31 ft. below land surface measured on mo/day/yr 08/10/93					
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 7.25 in. to ft. and in. to ft.							
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well			
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted						Water Well Disinfected? Yes X No			
5) TYPE OF BLANK CASING USED:		1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile	
2 PVC		4 ABS		7 Fiberglass		9 Other (specify below)		CASING JOINTS: Glued Clamped	
Blank casing diameter 2 in. to 15 ft., Dia		Casing height above land surface 42 in., weight		lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel		3 Stainless steel		5 Fiberglass		7 PVC	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)		10 Asbestos-cement	
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes		11 None (open hole)	
SCREEN-PERFORATED INTERVALS:		From 5.0 ft. to 14.5 ft.		From 14.5 ft. to 15.0 ft.					
GRAVEL PACK INTERVALS:		From 3'-10" ft. to 15.0 ft.		From 15.0 ft. to 15.0 ft.					
6) GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals: From 0.0 ft. to 2'-9" ft.		From 2'-9" ft. to 3'-10" ft.		From 3'-10" ft. to 15.0 ft.					
What is the nearest source of possible contamination:		1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		14 Abandoned water well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		15 Oil well/Gas well	
Direction from well?						13 Insecticide storage		16 Other (specify below) NONE	
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS							
0.0' 2.0' Fine to Medium Sand, Pale Brown									
2.0' 4.0' Fine to Medium Sand, Dark Brown									
4.0' 15.0' Fine to Coarse Sand, Pale Brown									
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/10/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 08/16/93 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									