

LOCATION OF WATER WELL: County: SEDGWICK		Fraction NE ¼ SW ¼ SW ¼	Section Number 21	Township Number T 28 S	Range Number R 1 E E/W
Distance and direction from nearest town or city street address of well if located within city? 527 E. 53rd St. S., Wichita, Ks.					
WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Leon Price 527 E. 53rd St. S. Wichita, Ks. Board of Agriculture, Division of Water Resources Application Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL 45 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 20 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL . . . 20 ft. below land surface measured on mo/day/yr 4-30-82			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter . . 11 in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No... X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . X . . Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Welded			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Threaded			
Blank casing diameter 5 in. to 25 ft., Dia in. to ft. Dia in. to ft.		Cer-Mac Styrene SDR-26 lbs./ft. Wall thickness or gauge No. 203			
Casing height above land surface 12 in., weight 1.59 lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 25 ft. to 45 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 14 ft. to 45 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		How many feet? 40			
Direction from well? South					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	18	Clay			
18	27	Clay and Gravel			
27	45	Medium Sand with Gravel			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-30-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-21-82 by (signature) M. Arnold					
under the business name of Harp Well & Pump Serv., Inc.					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					