


1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 SE 1/4 Section Number 21 Township Number T 28 S Range Number R 1 E
 County: Padgett

Distance and direction from nearest town or city street address of well if located within city?

1222 E 55th St

2 WATER WELL OWNER: Mrs. Smith
 RR#, St. Address, Box #: 1222 E 55th St
 City, State, ZIP Code: Wichita Kan 67216
 Board of Agriculture, Division of Water Resources
 Application Number: none

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 1300

Depth(s) Groundwater Encountered 1. 10 ft. 2. 10 ft. 3. 10 ft.

WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 7-2-91

Pump test data: Well water was 10 ft. after 1 hours pumping 10 gpm

Est. Yield 10 gpm: Well water was 10 ft. after 1 hours pumping 10 gpm

Bore Hole Diameter 9 in. to 10 ft., and 10 in. to 10 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X

Blank casing diameter 5 in. to 20 ft., Dia. 12 in. to 160 ft.

Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL: 2 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft., From 20 ft. to 30 ft.

GRAVEL PACK INTERVALS: From none ft. to 10 ft., From 10 ft. to 10 ft.

From 10 ft. to 10 ft., From 10 ft. to 10 ft.

From 10 ft. to 10 ft., From 10 ft. to 10 ft.

From 10 ft. to 10 ft., From 10 ft. to 10 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? E How many feet? 15

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 15 Fine tan sand 0 15

15 30 Coarse tan sand 15 30

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-2-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 472 This Water Well Record was completed on (mo/day/yr) 7-2-91 under the business name of Beardon Pump & Well Co. by (signature) David R. Beardon