


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SW 1/4 NE 1/4 NE 1/4	21	T 28 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 4931 S. Victoria, Wichita Price Truck Line, Inc. 3221 S. West Wichita KS 67217					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources Application Number:			
RR#, St. Address, Box # :					
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 9.54 ft. 2. 12 ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 9.54 ft. below land surface measured on mo/day/yr 5-13-93			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded Flashed			
5 Wrought iron 8 Concrete tile					
6 Asbestos-Cement 9 Other (specify below)					
7 Fiberglass					
Blank casing diameter 2 in. to ft., Dia		in. to ft., Dia			
Casing height above land surface Flashed in., weight 703 lbs./ft.		Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft.		ft. to ft.			
GRAVEL PACK INTERVALS: From 6 ft. to 17 ft.		ft. to ft.			
6 GROUT MATERIAL:		3 Bentonite 4 Other			
1 Neat cement 2 Cement grout					
Grout Intervals: From 6 ft. to 1 ft.		ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? South		How many feet? 25			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0.0 1.0 concrete					
1.0 6.5 Sand, Dark gray, very silty					
6.5 11.5 Sand, tan, med to fine					
11.5 17.0 Sand, w/ fine gravel					
Flush mount waiver granted 3-18-93 for Price Truck Line, Inc. by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-13-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 5-14-93 under the business name of GSI by (signature) Allison Irwin					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.