

1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 NE 1/4 Section Number 21 Township Number T 28 S Range Number R 10 E/W

Distance and direction from nearest town or city street address of well if located within city? 4931 S. Victoria, Wichita

2 WATER WELL OWNER: Price Truck Line, Inc. 3221 S. West Wichita KS 67217 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-acre section with an 'X' in the center, labeled 'X' in the center of the section box.]

4 DEPTH OF COMPLETED WELL: 16.5 ft. ELEVATION: 10 ft. WELL'S STATIC WATER LEVEL: 8.55 ft. below land surface measured on mo/day/yr 5-13-93

Pump test data: Well water was ... ft. after ... hours pumping ... gpm

Est. Yield ... gpm Well water was ... ft. after ... hours pumping ... gpm

Bore Hole Diameter: 8 in. to ... ft., and ... in. to ... ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush

Blank casing diameter: 2 in. to ... ft., Dia. in. to ... ft., Dia. in. to ... ft.

Casing height above land surface: Flush in, weight: 1703 lbs./ft. Wall thickness or gauge No. 154

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 6.5 ft. to 16.5 ft. From ... ft. to ... ft.

GRAVEL PACK INTERVALS: From 5.5 ft. to 16.5 ft. From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 5.5 ft. to 1 ft. From ... ft. to ... ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? SE How many feet? 125

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	3.0	Silt, dark brown, sandy, clayey			
3.0	8.5	Sand, tan & rust, fine to med			
8.5	13.5	Sand, med to coarse, tan			
13.5	16.5	Sand, tan, very coarse w/ fine to med gravel			

Flush mount waiver granted 3-18-93 for Price Truck Line, Inc by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-13-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 5-14-93 under the business name of ASI by (signature) Allison Krum