

1 LOCATION OF WATER WELL: County: <u>Seagwick</u>	Fraction: <u>SE 1/4 SW 1/4 SW 1/4</u>	Section Number: <u>21</u>	Township Number: <u>T 28 S</u>	Range Number: <u>R 10 E</u>
--	---------------------------------------	---------------------------	--------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: RR#, St. Address, Box # : <u>Marcella Barthelt</u> City, State, ZIP Code : <u>6309 S. Madison</u> <u>Wichita KS 67216</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>27</u> ft. ELEVATION:
--	---

	Depth(s) Groundwater Encountered 1. <u>8</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>8</u> ft. below land surface measured on mo/day/yr <u>2-23-93</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter in. to ft. and in. to ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped
1 Steel 3 RMP (SR)	Welded
2 PVC 5 ABS	Threaded
Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft.	
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No. <u>160 PVC</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 18 ft. to 27 ft. From ft. to ft. From ft. to ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From 12 ft. to 27 ft. From ft. to ft. From ft. to ft. From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 12 ft. From ft. to ft. From ft. to ft. From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? <u>SW.</u>	How many feet? <u>60'</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	5	clay			
5	25	good gravel			
25	27	blue clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-23-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>310</u> This Water Well Record was completed on (mo/day/yr) <u>2-23-93</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Susan K. Weninger</u>
