

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NW 1/4 SE 1/4 NE 1/4	28	T 28 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 5829 S. HYDRAULIC WICHITA KANSAS 67216					
2 WATER WELL OWNER: KEITH BAKER					
RR#, St. Address, Box #: 5829 S. HYDRAULIC				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: WICHITA, KANSAS 67216				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 10 ft. 2. 10 ft. 3. 10 ft.			
		WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 2-18-84			
		Pump test data: Well water was 10 ft. after 2 hours pumping 25 gpm			
		Est. Yield 50 gpm: Well water was 10 ft. after 2 hours pumping 25 gpm			
		Bore Hole Diameter: 9 in. to 3.4 ft. and 3.4 in. to 3.4 ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? ☒ Yes ☐ No			
5 TYPE OF BLANK CASING USED:					
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: ☒ Glued ☐ Clamped ☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐ Welded ☐ Blank casing diameter 5 in. to 14 ft. Dia. ☐ 7 Fiberglass ☐ Threaded					
Casing height above land surface: 12 in., weight 237 lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☐ 11 Other (specify) ☐ SCREEN OR PERFORATION OPENINGS ARE: ☐ 5 Gauzed wrapped ☒ 8 Saw cut ☐ 11 None (open hole) ☐ 1 Continuous slot ☐ 3 Mill slot ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 7 Torch cut ☐ 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 14 ft. to 34 ft. From 14 ft. to 34 ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 34 ft. From 10 ft. to 34 ft.					
6 GROUT MATERIAL: ☒ 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other					
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 10 ft.					
What is the nearest source of possible contamination:					
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage					
Direction from well? WEST How many feet? 60					
LITHOLOGIC LOG					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	30	SANDY LOAM TOPSOIL			
3	100	FINE SAND			
10	32	LOUVER SAND, SMALL GRAVEL			
32	34	CLAY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-18-84 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/year) 2-28-84					
under the business name of RALPH MIETZGER WELL DIGGERS INC.					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

D