

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgewick</u>		<u>SE 1/4 SE 1/4 NW 1/4</u>	<u>28</u>	<u>T 28 S</u>	<u>R 1 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>5907 S. Washington</u>					
2 WATER WELL OWNER: <u>John W. Walters</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: <u>5907 S. Washington</u>		Application Number: <u>NA</u>			
City, State, ZIP Code: <u>Wichita KS 67216</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>41'-4"</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>19</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>19</u> ft. below land surface measured on mo/day/yr <u>9-18-85</u>			
		Pump test data: Well water was <u>22</u> ft. after <u>2</u> hours pumping <u>25</u> gpm			
		Est. Yield <u>100</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>9</u> in. to <u>19</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No ☒ ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped			
1 Steel ☒ 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter <u>6</u> in. to <u>36</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface <u>12</u> in., weight <u>119.5</u> lbs./ft. Wall thickness or gauge No. <u>SDR 26</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass ☒ 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped ☒ 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>36</u> ft. to <u>41</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>15</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
☒ 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? <u>South West</u>		How many feet? <u>55</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Drk Brn Sand/clay loam			
3	16	LT TAN. Fine Sand			
19	31	Drk Gray fine Sand/clay mix			
31	32	Drk Gray clay			
32	41	LT Gray med-coarse Sand			
X 16	19	LT Gray med fine Sand & clay balls			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-18-85</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>295</u> This Water Well Record was completed on (mo/day/yr) <u>9-18-85</u>					
under the business name of <u>Protheroe Pump & Well Service</u> by (signature) <u>Glenn J. Protheroe</u>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4