			Water Well Recor	d Form WWC-5			
1 LOCATION OF W		FRACTION			Section Number	Township Number	Range Number
Sedg		NE 1/4		NE 1/4	29	т 28 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?							
	. Jones	Wichita, Ka	ansas				
2 WATER WELL		RTZ, Ben					
RR#, ST. ADRES		9 S. Jones				Board of Agriculture,	Divivsion of Water Resource
CITY, STATE, ZI	PCODE: Wic	<u>hita,Kansas</u>				Application Numb	er:
3 LOCATE WELL'S AN "X" IN SECTION	LOCATION WITH		MPLETED WELL	28		LEVATION:	
AN A INSECTION	N BOA:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.
		WELL'S STATIC W		2 FT.	BELOW LAND S	URFACE MEASURED ON mo/day/yr	03/01/1993
NW	NE	Pump tes	t data: Well	water was	ft.	after hours pur	mping gpm
	X	Est. Yield	gpm: Well	water was	ft.	after hours pur	mping gpm
w	E	Bore Hole Diameter	12 in.	to 28	ft.,	and in.	to ft.
		WELL WATER TO	BE USED AS:	5 Public water	r supply	8 Air conditioning 11	Injection well
₽sw	sæ	1 Domestic	3 Feedlot	6 Oil field wa		9 Dewatering 12	Other (Specify below)
i sw		2 Irrigation	4 Industrial	7 Lawn and g	arden only	10 Monitoring well	
		Was a chemical/bacte	riological sample su	ıbmitted to De	partment? Yes	No X ; If yes, i	mo/day/yr sample was
	S	submitted			W	ater Well Disinfected? Yes	X No
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel	3 RMP (SR)		6 Asbestos-Ceme	ent 9	Other (Specify	/	Welded
2 PVC	4 ABS		7 Fiberglass	S	DR-26	•	Threaded
Blank casing Diar	_	in. to 21	ft., Dia	in.	to	ft., Dia in.	to ft.
	ove land surface	,	weight	2.35	lbs. / ft.	Wall thickness or gauge No.	.214
	EN OR PERFORA	TION MATERIAL:			PVC	10 Asbestos-cen	ient
1 Steel	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specif	y)
2 Brass 4 Galvanized steel 6 Concr				oncrete tile 9 ABS		12 None used (o	pen hole)
SCREEN OR PE	RFORATION OP	ENING ARE:		5 Gauzed wrapped		8 Saw cut 11 None (open hole)	
1 Continous slot	6 Wire	6 Wire wrapped 9 Dr					
2 Louvered shutt	er 4 Key p	unched	7 Torc	h cut		10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 21 ft. to 28 ft., From ft. to ft.							
į		from	ft	. to	ft., Fro	m ft. to	ft.
GRAVEL PACK INTERVALS: from 20			ft. to 28		ft., Fro	om ft. to	ft.
		from	ft	. to	ft., Fro	om ft. to	ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals:	ft., From	ft.	to	ft., From	ft. to ft.		
What is the nearest source of possible contamination:						tock pens 14.	Abandon water well
1 Septic tank 4 Lateral lines						nel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lage				Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent							
Direction form well? How many feet?							
FROM TO		LITHOLOGIC LOG		FROM	ТО	PLUGGING INTE	
0 3	topsoil						SYSTEM NOT
3 9	clay				 	INSTALLED AT THE	HIS TIME
9 20	fine sar			<u> </u>		· · · · · · · · · · · · · · · · · · ·	
20 28	medium s	sand			1		
	.						Santa Control of the
	_						
	 						
					<u> </u>		
		о. н.					
					+		
							
<u> </u>	<u> </u>				1		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed	on (mo/day/year)	03/01/	1993	and this rec	ord is true to t	the best of my knowledge and	l belief. Kansas Water
Well Contracto	r's License No	236	This Water Well R	ecord was co	ompleted on (r	mo/dav/vr) 04/0	18/93
Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick							
335							