WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	SW ¼ SW ¼ SE ¼	31	T 28 S	R 1 E/W

Distance and direction from nearest town or city? Street address of well if located within city? 612 Chrestline

2 WATER WELL OWNER: Mike Schmidtt
RR#, St. Address, Box # 612 Chrestline
City, State, ZIP Code Haysville Kans

Board of Agriculture, Division of Water Resources Application Number:

3 DEPTH OF COMPLETED WELL [redacted]-40 ft. Bore Hole Diameter [redacted] 8 in. to 30 ft., and 8 in. to 40 ft.

Well Water to be used as: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)

Well's static water level 20 ft. below land surface measured on 6 month 12 day 1980 year

Pump Test Data: Well water was – ft. after – hours pumping gpm
Est. Yield 10 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Styrene 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)

Casing Joints: Glued Clamped Welded Threaded

Blank casing dia 4 in. to ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 100 lbs./ft. Wall thickness or gauge No 14

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) slotted 12 None used (open hole)

Screen or Perforation Openings Are: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 35-40 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

Screen-Perforation Dia 4 in. to [redacted] ft., Dia [redacted] in. to ft., Dia in to ft.

Screen-Perforated Intervals: From ft. to ft., From ft. to ft.
From ft. to ft., From ft. to ft.

Gravel Pack Intervals: From no ft. to ft., From ft. to ft.
From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines Sealed 3 Lateral lines 4 Cess pool 5 Seepage pit 6 Pit privy 7 Sewage lagoon 8 Feed yard 9 Livestock pens 10 Fuel storage 11 Fertilizer storage 12 Insecticide storage 13 Watertight sewer lines 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well West How many feet 12? Water Well Disinfected? Yes ✓ No

Was a chemical/bacteriological sample submitted to Department? Yes No ✓ If yes, date sample was submitted month day year: Pump Installed? Yes No

If Yes: Pump Manufacturer's name Model No. HP Volts

Depth of Pump Intake ft. Pumps Capacity rated at gal./min.

Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on June month 12 day 1980 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 313

This Water Well Record was completed on June month 12 day 1980 year under the business name of Jet Drilling by (signature) Virgil Sandman

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



ELEVATION:

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	30	Black Clay			
30	40	Red Gravel			

Depth(s) Groundwater Encountered 1. 20 ft. 2. 40 ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 28 R 1 E/W SEC. 31 SW ¼ SW ¼ SE ¼