

1 LOCATION OF WATER WELL: County: <u>SEDC</u>		Fraction: <u>1/4 NW 1/4 Sec 31</u>	Section Number: <u>31</u>	Township Number: <u>T 28 S</u>	Range Number: <u>R 1 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>SAME</u>					
2 WATER WELL OWNER: <u>LYNN Bueckamp</u> RR#, St. Address, Box #: <u>419 Linden Ct.</u> City, State, ZIP Code: <u>Haysville, KS</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>35</u> ft. ELEVATION: <u>1152</u>			
		Depth(s) Groundwater Encountered 1. <u>18</u> ft. 2. <u>18</u> ft. 3. <u>18</u> ft. WELL'S STATIC WATER LEVEL <u>18</u> ft. below land surface measured on mo/day/yr <u>8-1-91</u> Pump test data: Well water was <u>18</u> ft. after <u>2</u> hours pumping <u>10</u> gpm Est. Yield <u>30</u> gpm: Well water was <u>18</u> ft. after <u>2</u> hours pumping <u>10</u> gpm Bore Hole Diameter <u>10</u> in. to <u>35</u> ft. and <u>10</u> in. to <u>35</u> ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes <u>No</u>			
		TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>Clamped</u> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded.			
Blank casing diameter <u>5</u> in. to <u>25</u> ft. Dia. <u>12</u> in. weight <u>2</u> lbs./ft. Wall thickness or gauge No. <u>SA 4</u>		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		SCREEN-PERFORATED INTERVALS: From <u>25</u> ft. to <u>35</u> ft. From <u>18</u> ft. to <u>35</u> ft. GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>35</u> ft. From <u>18</u> ft. to <u>35</u> ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>2</u> ft. to <u>18</u> ft. From <u>18</u> ft. to <u>35</u> ft. From <u>18</u> ft. to <u>35</u> ft. From <u>18</u> ft. to <u>35</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>None noted</u>					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
2		18		clay	
18		25		med sand	
25		35		gravel ✓	
7 CONTRACTOR'S OR LANDOWNERS CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-1-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>463</u> This Water Well Record was completed on (mo/day/yr) <u>8-25-91</u> under the business name of <u>LSA</u> by (signature) <u>Don P. K.</u>					