

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: NW 1/4 SE 1/4 NW 1/4 Section Number: 32 Township Number: T 28 S Range Number: R 1E E/W

Distance and direction from nearest town or city street address of well if located within city? Not Related

2 WATER WELL OWNER: RR#, St. Address, Box #: Walters - Morgan City, State, ZIP Code: P. O. Box 849, Manhattan, Kansas 66502 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NW corner]

4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 10 ft. below land surface measured on mo/day/yr 6-1-83

Depth(s) Groundwater Encountered 1. 25 ft. after 1 hours pumping 900 gpm

WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 6-1-83

Pump test data: Well water was 25 ft. after 1 hours pumping 900 gpm

Est. Yield 500 gpm: Well water was 30 ft. after 1 hours pumping 900 gpm

Bore Hole Diameter 3.6 in. to 3.0 ft. and 3.0 in. to 3.0 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter 12 in. to 18 ft. Dia 12 in. to 18 ft. Dia

Casing height above land surface 2 ft. in. weight 12 lbs./ft. Wall thickness or gauge No. 25

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut

SCREEN-PERFORATED INTERVALS: From 18 ft. to 30 ft. From 18 ft. to 30 ft. From 18 ft. to 30 ft. From 18 ft. to 30 ft.

GRAVEL PACK INTERVALS: From 18 ft. to 30 ft. From 18 ft. to 30 ft. From 18 ft. to 30 ft. From 18 ft. to 30 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 18 ft. to 30 ft. From 18 ft. to 30 ft. From 18 ft. to 30 ft. From 18 ft. to 30 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 15 COARSE SAND

15 16 CLAY

16 19 COARSE SAND

19 20 SILT

20 30 COARSE SAND

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 445-A This Water Well Record was completed on (mo/day/yr) 6-1-83 under the business name of KELLEY CONTRACT DEWATERING COMPANY by (signature) Barry Mefford

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.