

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 SE 1/4 Section Number 33 Township Number T 28 S Range Number R 1 E
 County: Sedg. Distance and direction from nearest town or city street address of well if located within city? See below

2 WATER WELL OWNER: Ralph Harvoston
 RR#, St. Address, Box #: 1432 E 71st So.
 City, State, ZIP Code: Haysville KS
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
---	NW	---	NE
---		---	
---	SW	---	SE
---		---	
S		E	

4 DEPTH OF COMPLETED WELL 30 ft. ELEVATION: 12-13-85
 Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 12-13-85
 Pump test data: Well water was 16 ft. after 12 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 16 ft. after 12 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 30 ft., and 30 in. to 30 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted No
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel ☐ 3 RMP (SR) ☒ 5 Wrought iron ☐ 8 Concrete tile ☐
 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐
 7 Fiberglass ☐
 Blank casing diameter 5 in. to 18 ft., Dia 18 in. to 30 ft., Dia 30 in. to 30 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 7 PVC ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☒ 11 Other (specify) ☐
 9 ABS ☐ 12 None used (open hole) ☐
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☒ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 7 Torch cut ☐ 10 Other (specify) ☐
 SCREEN-PERFORATED INTERVALS: From 18 ft. to 30 ft., From 18 ft. to 30 ft., From 18 ft. to 30 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 30 ft., From 13 ft. to 30 ft., From 13 ft. to 30 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
 Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 30 ft., From 13 ft. to 30 ft., From 13 ft. to 30 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐
☐ 13 Insecticide storage ☐
 Direction from well? No. How many feet? 125

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	14	Clay			
14	28	Sand			
28	30	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-13-85 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 3188 This Water Well Record was completed on (mo/day/yr) 12-13-85
 under the business name of Wenger Pully by (signature) Wenger
 INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.