


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 SE 1/4 Section Number 34 Township Number T 28 S Range Number R 1 EW
 County: SIEDGWICK

Distance and direction from nearest town or city street address of well if located within city?

7021 S LORRAIN WICHITA KANSAS 67216

2 WATER WELL OWNER: STELLA GUINN
 RR#, St. Address, Box #: 2639 MASON TERRACE
 City, State, ZIP Code: WICHITA, KANSAS 67216
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 28 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 11 ft. 2. 11 ft. 3. 11 ft.

WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 3-3-84

Pump test data: Well water was 11 ft. after 2 hours pumping 36 gpm

Est. Yield 70 gpm: Well water was 11 ft. after 2 hours pumping 36 gpm

Bore Hole Diameter 11 in. to 11 in. and 2 in. to 2 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ✓ No ✓

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 12 in. Dia 12 in. to 12 in. Dia 12 in. to 12 in. Dia

Casing height above land surface 12 in. weight 2.37 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 12 ft. to 28 ft. From 12 ft. to 28 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 28 ft. From 10 ft. to 28 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? 75 NORTH EAST How many feet? 75

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 4 DARK TOP SOIL 0 4 DARK TOP SOIL

4 8 FINE SAND STREAKS OF CLAY 4 8 FINE SAND STREAKS OF CLAY

8 16 FINE SAND 8 16 FINE SAND

16 28 COURSE SAND SMALL GRAVEL 16 28 COURSE SAND SMALL GRAVEL

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-3-84 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 3-6-84

under the business name of RALPH METZGER WELL DIGGING

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.