

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>SEDGWICK</u>		<u>NW 1/4 NE 1/4 NE 1/4</u>	<u>35</u>	T <u>28</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well, if located within city? <u>5539 S. OLIVER Wichita, KS 67037</u>					
2 WATER WELL OWNER: <u>STEVIE NEAL</u>					
RR#, St. Address, Box #: <u>6539 S. OLIVER</u>					
City, State, ZIP Code: <u>WICHITA, KS 67037</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>36</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>24</u> ft. 2. <u>24</u> ft. 3. <u>24</u> ft.			
		WELL'S STATIC WATER LEVEL <u>24</u> ft. below land surface measured on mo/day/yr <u>5-14-91</u>			
		Pump test data: Well water was <u>24</u> ft. after <u>2</u> hours pumping <u>20</u> gpm			
		Est. Yield <u>30</u> gpm: Well water was <u>36</u> ft. after <u>2</u> hours pumping <u>20</u> gpm			
		Bore Hole Diameter <u>11</u> in. to <u>36</u> ft. and <u>36</u> in. to <u>36</u> ft.			
WELL WATER TO BE USED AS:					
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7 Lawn and garden only</u> 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ✓; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>✓</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>✓</u> Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded					
Blank casing diameter <u>5</u> in. to <u>26</u> ft. Dia <u>2.37</u> in. to <u>2.50</u> ft. Dia <u>2.50</u> in. to <u>2.50</u> ft.					
Casing height above land surface <u>16</u> in., weight <u>2.37</u> lbs./ft. Wall thickness or gauge No. <u>250</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped <u>8 Saw cut</u> 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>26</u> ft. to <u>36</u> ft. From <u>26</u> ft. to <u>36</u> ft. From <u>26</u> ft. to <u>36</u> ft.					
GRAVEL PACK INTERVALS: From <u>22</u> ft. to <u>36</u> ft. From <u>22</u> ft. to <u>36</u> ft. From <u>22</u> ft. to <u>36</u> ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>0-3' SURFACE SOIL</u> Grout Intervals: From <u>3</u> ft. to <u>22</u> ft. From <u>22</u> ft. to <u>36</u> ft. From <u>36</u> ft. to <u>36</u> ft. From <u>36</u> ft. to <u>36</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>South</u> How many feet? <u>500</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	SURFACE SOIL			
2	14	CLAY			
14	28	FINE SAND			
28	35	COURSE SAND			
35	36	WILLINGTON SHALE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-14-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>437</u> This Water Well Record was completed on (mo/day/yr) <u>5-30-91</u> under the business name of <u>RALPH THETZGER WELL DIGGER DRILLING</u> <u>Ralph A. Metzger</u>					