


1 LOCATION OF WATER WELL: Sedgwick	FRACTION <i>SW NE NE SW</i> SE 1/4 SW 1/4 SW 1/4	Section Number 36	Township Number T 28 S	Range Number R 1E E/W
--	--	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1033 N. Buckner Derby, Kansas

2 WATER WELL OWNER: 1ST NATIONAL BANK OF DERBY	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 1033 N. Buckner	Application Number:
CITY, STATE, ZIP CODE: Derby, Kansas	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 85 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 60 FT. BELOW LAND SURFACE MEASURED ON 06/15/1994	
Pump test data: Well water was ft. after hours pumping gpm	
Est. Yield gpm: Well water was ft. after hours pumping gpm	
Bore Hole Diameter 12 in. to 85 ft. and in. to ft.	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes X No	

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued X Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Welded	
2 PVC 4 ABS	7 Fiberglass	SDR-26	Threaded	
Blank casing Diameter 5 in. to 65 ft., Dia	in. to ft., Dia	in. to ft., Dia	in. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft.		Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel 3 Stainless Steel 5 Fiberglass	6 Concrete tile 9 ABS	7 PVC 8 RMP (SR)	10 Asbestos-cement 11 other (specify)	12 None used (open hole)
2 Brass 4 Galvanized steel	6 Concrete tile 9 ABS			
SCREEN OR PERFORATION OPENING ARE:				
1 Continuous slot 3 Mill slot	5 Gauzed wrapped 6 Wire wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter 4 Key punched	7 Torch cut	9 Drilled holes	10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 65 ft. to 85 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: from 24 ft. to 85 ft., From ft. to ft.				

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank 4 Lateral lines 7 Pit privy	8 Sewage lagoon	9 Feedyard	10 Livestock pens 11 Fuel storage	12 Fertilizer storage 13 Insecticide storage
2 Sewer lines 5 Cess pool				14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit				None Apparent

Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	60	clay			
60	65	fine sand			
65	78	medium sand			
78	85	grey shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/15/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/17/94 Under the business name of Harp Well & Pump Service, Inc by (signature) Jane Frederick