

I LOCATION OF WATER WELL: County: SEDGWICK		Fraction SE ¼ SW ¼ NW ¼	Section Number 36	Township Number T 28 S	Range Number R 1 E EW
Distance and direction from nearest town or city street address of well if located within city? 6630 SE Blvd. Wichita, Kansas					
II WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		K-15 Storage 6630 S.E. Blvd. Derby, Kanss		Board of Agriculture, Division of Water Resources Application Number:	
III LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		IV DEPTH OF COMPLETED WELL..... 75 ft. ELEVATION:			
A vertical scale bar indicates 1 mile. A horizontal scale bar indicates 1 mile.		Depth(s) Groundwater Encountered 1. 45 ...ft. 2.ft. 3.ft. WELL'S STATIC WATER LEVEL 45 ...ft. below land surface measured on mo/day/yr 10-24-89			
		Pump test data: Well water wasft. after hours pumping gpm Est. Yield gpm: Well water wasft. after hours pumping gpm Bore Hole Diameter 11 .in. toft., andin. toft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well If yes, mo/day/yr sample was submitted Yes.....No....XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No			
V TYPE OF BLANK CASING USED:		CASING JOINTS:			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile Glued . XX Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Cer-Mac styrene SDR-26 Threaded			
Blank casing diameter 12 ...in. to 55 ...ft., Diain. toft., Diain. toft. Casing height above land surface 12 ...in., weight ... 1.59 ...lbs./ft. Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile		7 PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 55 ...ft. to 75 ...ft., Fromft. toft.			
GRAVEL PACK INTERVALS:		From 24 ...ft. to 75 ...ft., Fromft. toft.			
VI GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 4 ...ft. to 24 ...ft., Fromft. toft., Fromft. toft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage			
Direction from well? N.W.		How many feet? 200			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	50	Clay			
50	63	Fine Sand to Medium Sand			
63	75	Gray Shale			
VII CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-24-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 4-1-90 under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					