


1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ NE $\frac{1}{4}$ SE $\frac{1}{4}$ Section Number 30 Township Number T 28 S Range Number R 1

County: SEDGWICK SE Distance and direction from nearest town or city street address of well if located within city: 1 1/4 MILE N. OF HAYSVILLE 6141 S. SENIKA Wichita KS

2 WATER WELL OWNER: ROSE CODY RR#, St. Address, Box #: 5420 W. 37 ST. SOUTH City, State, ZIP Code: WICHITA KANSAS 67215 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION: 9-18-82

Depth(s) Groundwater Encountered 1. 13 ft. 2. 13 ft. 3. 2 ft.

WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 9-18-82

Pump test data: Well water was 13 ft. after 2 hours pumping 40 gpm

Est. Yield 6.5 gpm; Well water was 26 ft. after 2 hours pumping 40 gpm

Bore Hole Diameter 9 in. to 26 ft., and 26 in. to 26 ft.

WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter 5 in. to 16 ft., Dia. 1.43 in. to 2.40 lbs./ft. Wall thickness or gauge No. 240

Casing height above land surface 14 in., weight 1.43

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

7 Torch cut

SCREEN-PERFORATED INTERVALS: From 16 ft. to 26 ft. From 13 ft. to 26 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 26 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other SURFACE SILTS 0-3 FT

Grout Intervals: From 13 ft. to 0 ft. From 0 ft. to 3 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? NORTH How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	SANDY LOAM SOIL			
2	4	SILT			
4	13	FINE SAND			
13	18	SAND, YELLOW IN COLOR			
18	26	SAND, GREY IN COLOR			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 10-3-82 under the business name of RALPH MIETZGER WALL DIGGER DRILLING (Signature) Ralph A. Mietzger

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.