


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 SW 1/4 SE 1/4	Section Number 32	Township Number T 28S S	Range Number R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 miles East from Haysville, on North side.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Clearwater Excavating Inc. Clearwater, KS 67026		Well #1 Board of Agriculture, Division of Water Resources Application Number: T80-190	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">  </div>		4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. 8 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 3/31/80 NO Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 20 in. to 48 in. to in. to in. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass		CASING JOINTS: Glued Clamped Welded X Threaded.....	
Blank casing diameter 16 in. to 0-10 in. Dia. in. to in. Dia. in. to in. Dia. in. to in.		Casing height above land surface 12 in., weight 31.66 lbs./ft. Wall thickness or gauge No. 188			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 10 ft. to 48 ft. From ft. to ft. From ft. to ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other NONE		Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage NONE		Direction from well? How many feet?			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	3	Top Soil			
3	6	Clay			
6	15	Medium sand			
15	18	Clay			
18	48	Medium sand			
THIS WELL HAS NOT BEEN PULLED OR PLUGGED, IT IS STILL EXISTING.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/21/80 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 9/15/82 under the business name of Rosencrantz-Bemis by (signature) Mike Powers					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4