

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 32	Township Number T 28S S	Range Number R 1W EW
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 miles East from Haysville, on North side.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Clearwater Excavating Inc. Well #2 Clearwater, KS 67026		Board of Agriculture, Division of Water Resources Application Number: T80-190	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 8 ft. 2. 8 ft. 3. 8 ft. WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 4/7/82 NO Pump test data: Well water was 8 ft. after 4 hours pumping 8 gpm Est. Yield 8 gpm: Well water was 8 ft. after 4 hours pumping 8 gpm Bore Hole Diameter 20 in. to 50 ft., and 50 in. to 50 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply <u>9 Dewatering</u> 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> 3 RMP (SR) 4 ABS Blank casing diameter 16 in. to 0-10 ft., Dia 0-10 in. to 0-10 ft., Dia 0-10 in. to 0-10 ft. Casing height above land surface 12 in., weight 31.66 lbs./ft. Wall thickness or gauge No. 188		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL: <u>1 Steel</u> 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 10 ft. to 50 ft., From 10 ft. to 50 ft., From 10 ft. to 50 ft. GRAVEL PACK INTERVALS: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other NONE Grout Intervals: From 0 ft. to 0 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage NONE		Direction from well? How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Top Soil			
3	6	Clay			
6	15	Medium sand			
15	18	Clay			
18	48	Medium sand			
PULLED AND PLUGGED ACCORDING TO STATE SPECIFICATIONS					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) XX 4/7/82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 9/15/82 under the business name of Rosencrantz-Bemis Ent. by (signature) Mike Hawks					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					