

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedwick	SW $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$	17	T 28 S	R 1 E	W

Distance and direction from nearest town or city street address of well if located within city?

1900' SE of Seneca and MacArthur, Wichita, Ks.

2	WATER WELL OWNER:	Oxy, Inc.	
	RR#, St. Address, Box # :	P.O. Box 300	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Tulsa, OK 74102	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: approx. 1280 MSL

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 8.92 ft. below land surface measured on mo/day/yr 05-23-94

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 20 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ X

If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒ X

5] TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded. ☒

Blank casing diameter 2 in. to 5 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. . . . sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 5 ft. to 20 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 3 ft. to 20 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:				1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:		From	0	ft. to	1	ft.	From
					1	ft. to	3
							ft. to
What is the nearest source of possible contamination:				10 Livestock pens		14 Abandoned water well	
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage	
Direction from well?		northwest		How many feet?		800	
						15 Oil well/Gas well	
						16 Other (specify below)	
						former refinery	

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05-05-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 06-16-94 under the business name of GeoCore Services, Inc. by (signature) [Signature]