

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Sedgwick		NE 1/4 SE 1/4 SE 1/4		21		T 28 S		R 1 SW			
Distance and direction from nearest town or city street address of well if located within city?											
350 ft. West of 5439 S. Hydraulic, Wichita, KS EAST											
2 WATER WELL OWNER: Meyers Garden Spot											
RR#, St. Address, Box # : 5439 S. Hydraulic Board of Agriculture, Division of Water Resources											
City, State, ZIP Code : Wichita, KS Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: Unknown									
		Depth(s) Groundwater Encountered 1. 35 ft. 2. ft. 3. ft.									
		WELL'S STATIC WATER LEVEL 1.5 ft. below land surface measured on mo/day/yr 7-7-94									
		Pump test data: Well water was NA ft. after hours pumping gpm									
		Est. Yield gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter: 14 1/4 in. to 50 ft., and in. to									
WELL WATER TO BE USED AS:											
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes X No											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded											
Blank casing diameter 8 in. to 30 in. Dia. in. to ft. Dia. in. to ft.											
Casing height above land surface 12 in. weight lbs./ft. Wall thickness or gauge No. SDR 26											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft. From ft. to ft.											
GRAVEL PACK INTERVALS: From 20 ft. to 50 ft. From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Water-tight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage											
Direction from well? East How many feet? 350 ft.											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		1		Top Soil							
1		20		Clay							
20		40		Sand							
40		50		Grey Shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) July 7, 1994 and this record is true to the best of my knowledge and belief. Kansas											
Water Well Contractor's License No. 464 This Water Well Record was completed on (mo/day/yr) 7-9-94											
under the business name of WATER WELL SERVICES by (signature) <i>Robert L. Shaw</i>											