

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NE 1/4 NE 1/4 NE 1/4		Section Number 17	Township Number T 28 S		Range Number R 1 EW	
Distance and direction from nearest town or city street address of well if located within city? 4003 South Broadway, Wichita, Kansas								
2 WATER WELL OWNER: Town & Country Markets		01948033		MW-6				
RR#, St. Address, Box # : P.O. Box 17087		Board of Agriculture, Division of Water Resources						
City, State, ZIP Code : Wichita, Kansas 67217		Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 17.0 ft. ELEVATION: Approx. 1281.0						
		Depth(s) Groundwater Encountered 1. 10.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 10.5 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 17 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded						
2 PVC 4 ABS		7 Fiberglass Threaded X						
Blank casing diameter 2 in. to 7 ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 7.0 ft. to 17 ft., From ft. to ft.		GRAVEL PACK INTERVALS: From 5.5 ft. to 17 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 3.5 ft., From 3.5 ft. to 5.5 ft., From ft. to ft.						
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well		3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
Direction from well?		How many feet?						
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS		0.0 0.4 Asphalt						
0.4 1.0 Limestone Screenings		1.0 8.5 Dark Brown, Sandy Lean Clay						
8.5 12.0 Gray-Brown, Fine to Medium Sand		12.0 17.0 Gray-Brown, Fine to Coarse Sand						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/07/94 and this record is true to the best of my knowledge and belief. Kansas		Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10-7-94 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								