

1 LOCATION OF WATER WELL: 287 Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 7 Township Number T 28 S Range Number R 1 E

Distance and direction from nearest town or city street address of well if located within city?


2433 W. 31st, Wichita

2 WATER WELL OWNER: BDAT Environmental
RR#, St. Address, Box #: 1862 Craigshire
City, State, ZIP Code: St. Louis, MO 63146

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 14.4 ft. ELEVATION: 1286.83

Depth(s) Groundwater Encountered 1. 9.49 ft. 2. 9 ft. 3. 8-31-93 ft.

WELL'S STATIC WATER LEVEL 9.49 ft. below land surface measured on mo/day/yr 8-31-93

Pump test data: Well water was N/A ft. after N/A hours pumping N/A gpm

Est. Yield N/A gpm: Well water was N/A ft. after N/A hours pumping N/A gpm

Bore Hole Diameter 6.75 in. to 15 in. and 15 in. to 15 in. ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well BW-4

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued No Clamped No

6 Asbestos-Cement

9 Other (specify below)

Welded No

7 Fiberglass

Threaded X

Blank casing diameter 2 in. to 4.4 in. ft., Dia 4.4 in. to 4.4 in. ft., Dia 4.4 in. to 4.4 in. ft.

Casing height above land surface 0 in., weight 0 lbs./ft. Wall thickness or gauge No. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 4 ft. to 14.4 ft. From 4 ft. to 14.4 ft. From 4 ft. to 14.4 ft.

GRAVEL PACK INTERVALS: From 2 ft. to 14.4 ft. From 2 ft. to 14.4 ft. From 2 ft. to 14.4 ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 2 ft. From 1 ft. to 2 ft. From 1 ft. to 2 ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? E

How many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1</u>	<u>Concrete</u>			
<u>1</u>	<u>3</u>	<u>Sandy Silty Clay (Fill)</u>			
<u>3</u>	<u>7</u>	<u>Sandy Silty Clay</u>			
<u>7</u>	<u>13</u>	<u>Clay</u>			
<u>13</u>	<u>15</u>	<u>Sand</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-31-93 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 571 This Water Well Record was completed on (mo/day/yr) 2-2-95

under the business name of BDAT Environmental, Inc. by (signature) By: [Signature]

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4