

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 4 Township Number: 28 Range Number: 1 EAST Distance and direction from nearest town or city street address of well if located within city? 1535 E. PAWNEE WICHITA, KANSAS Air Sparge #17

2 WATER WELL OWNER: FINA OIL & COMPANY RR#, St. Address, Box #: P.O. BOX 2159 DALLAS, TEXAS 75221 Board of Agriculture, Division of Water Resources City, State, ZIP Code Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section]

4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION: 17 ft. WELL'S STATIC WATER LEVEL: 17 ft. below land surface measured on mo/day/yr Pump test data: Well water was 7.4 in. to 26 ft. after 2.6 hours pumping Est. Yield 7.4 gpm: Well water was 2.6 ft. after 2.6 hours pumping Bore Hole Diameter 7.4 in. to 26 ft. and 2.6 in. to 26 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Sparge Point Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 9 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter 2 in. to 24 ft. Dia. in. to 24 ft. Dia. in. to 24 ft. Dia. in. to 24 ft. Casing height above land surface -3 in., weight Sched 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 3 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 26 ft. to 24 ft. From 26 ft. to 24 ft. From 26 ft. to 24 ft. From 26 ft. to 24 ft. GRAVEL PACK INTERVALS: From 26 ft. to 22 ft. From 26 ft. to 22 ft. From 26 ft. to 22 ft. From 26 ft. to 22 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 18 ft. to 0.6 ft. From 22 ft. to 18 ft. From 22 ft. to 18 ft. From 22 ft. to 18 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? North How many feet? 10'

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-20-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 1-15-95 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.