

1 LOCATION OF WATER WELL:		Fracture	Section Number	Township Number	Range Number
County: SEDGWICK 087		NE 1/4 NE 1/4 NE 1/4	4	T 28 S	R 1 E/W EAST
Distance and direction from nearest town or city street address of well if located within city? 1535 E. PAWNEE WICHITA, KANSAS Vapor Extraction Well # 2					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #		FINA OIL & COMPANY		Application Number:	
City, State, ZIP Code		P.O. BOX 2159 DALLAS, TEXAS 75221			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 1/4 in. to 20 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Vapor Extraction Well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 XPVC 4 ABS		Threaded			
Blank casing diameter 2 1/2 in. to 10 ft. Dia		in. to ft. Dia in. to ft.			
Casing height above land surface -3 in. weight Sched 40 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass XPVC		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot Mill slot		9 Drilled holes			
2 Louvered shutter 4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 20 ft. to 10 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 8 ft. From ft. to ft.					
6 GROUT MATERIAL:		4 Other			
1 Neat cement Cement grout Bentonite					
Grout Intervals: From 7 ft. to 1.0 ft. From 8 ft. to 7 ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? SW		How many feet? 45			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	CONCRETE			
6"	3'	TOP SOIL			
3'	9'	Brn Clay			
9'	14'	FINE SAND			
14'	20'	MEDIUM SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-20-95 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 1-15-95					
under the business name of ROUTE ENVIRONMENTAL SERVICE by (signature) MA 154					