

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK 087		NE 1/4 NE 1/4 NE 1/4	4	T 28 S	R 1 EAST
Distance and direction from nearest town or city street address of well if located within city? 1535 E. PAWNEE WICHITA, KANSAS Air Sparge # 7					
2 WATER WELL OWNER:					
RR#, St. Address, Box #: FINA OIL & COMPANY				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: P.O. BOX 2159 DALLAS, TEXAS 75221				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 1/4 in. to 26 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Spargers			
Was a chemical/bacteriological sample submitted to Department? Yes No		If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
Blank casing diameter 2" in. to 24" ft. Dia				7 Fiberglass	
Casing height above land surface -3" in., weight Steel 40 lbs./ft.				8 Concrete tile	
TYPE OF SCREEN OR PERFORATION MATERIAL:				9 Other (specify below)	
1 Steel		3 Stainless steel		10 Asbestos-cement	
2 Brass		4 Galvanized steel		11 Other (specify)	
3 Fiberglass		6 Concrete tile		12 None used (open hole)	
4 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		6 Wire wrapped		11 None (open hole)	
2 Louvered shutter		7 Torch cut		9 Drilled holes	
3 Mill slot				10 Other (specify)	
4 Key punched					
SCREEN-PERFORATED INTERVALS:		From 26 ft. to 24 ft.		From ft. to ft.	
		From ft. to ft.		From ft. to ft.	
GRAVEL PACK INTERVALS:		From 26 ft. to 22 ft.		From ft. to ft.	
		From ft. to ft.		From ft. to ft.	
6 GROUT MATERIAL:					
1 Neat cement		3 Cement grout		5 Bentonite	
Grout Intervals: From 18 ft. to 0.6 ft.		From 22 ft. to 18 ft.		4 Other	
What is the nearest source of possible contamination:				10 Livestock pens	
1 Septic tank		4 Lateral lines		14 Abandoned water well	
2 Sewer lines		5 Cess pool		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		16 Other (specify below)	
7 Pit privy		8 Sewage lagoon		13 Insecticide storage	
9 Feedyard					
Direction from well? West				How many feet? 79'	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	Concrete			
6"	3'	Top soil			
3'	9'	Brn Clay			
9'	14'	Fine Sand			
14'	20'	Med Sand			
20'	26'	Med To Coarse Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-17-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 1-17-95 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature) [Signature]					