

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction: NE 1/4	NE 1/4	NE 1/4	Section Number: 4	Township Number: T 28 S	Range Number: R 1	EAST
Distance and direction from nearest town or city street address of well if located within city? 1535 E. PAWNEE WICHITA, KANSAS								
2 WATER WELL OWNER: FINA OIL & COMPANY RR#, St. Address, Box #: P.O. BOX 2159 DALLAS, TEXAS 75221 Board of Agriculture, Division of Water Resources City, State, ZIP Code: Application Number:								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION:					
1 Mile N W E S NE NW SE SW X			Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/4 in. to 26 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering * Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Sparge Point Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped * PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 1/2 in. to 24 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface -3 in. weight Sched 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: * PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot * Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 26 ft. to 24 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 26 ft. to 22 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout * Bentonite 4 Other Grout Intervals: From 18 ft. to 0.6 ft. From 22 ft. to 18 ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy * Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? SW How many feet? 65'								
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0 6" Concrete								
6" 3' Top Soil								
3' 9' Brown Clay								
9' 14' Fine Sand								
14' 20' Med To Coarse Sand								
20' 26' Med To Coarse Sand								
Gravel								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-18-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 7-11-95 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								