

1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 NE 1/4 Section Number 1426 Township Number 28 Range Number 27 S 12 R 3 E/W

County: Greenwood

Distance and direction from nearest town or city street address of well if located within city? 2 M West of Fall River

2 WATER WELL OWNER: Haskel Fogle White Ran

RR#, St. Address, Box #: 2324 West 13th 67203

City, State, ZIP Code: 2324 West 13th 67203

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION: 30 ft. below land surface measured on mo/day/yr

Depth(s) Groundwater Encountered 1. 65 ft. 2. 30 ft. 3. 30 ft.

WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 20 gpm Well water was 85 ft. after 13 hours pumping 20 gpm

Est. Yield 20 gpm Well water was 85 ft. after 13 hours pumping 20 gpm

Bore Hole Diameter: 8 1/2 in. to 85 ft., and 13 in. to 200 ft.

WELL WATER TO BE USED AS:

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X

Blank casing diameter 5 in. to 50 ft., Dia 50 in. to 200 ft., Dia 200 in. to 214 ft.

Casing height above land surface 18 in., weight 200 lbs./ft. Wall thickness or gauge No. 12.4

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

SCREEN-PERFORATED INTERVALS: From 50 ft. to 85 ft., From 85 ft. to 200 ft.

GRAVEL PACK INTERVALS: From 50 ft. to 85 ft., From 85 ft. to 200 ft.

6 GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 85 ft., From 85 ft. to 200 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? E How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	SOIL			
4	15	ROCK			
15	25	SHALE			
25	85	Lime gas at 80'			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/14/86 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 251 This Water Well Record was completed on (mo/day/yr) 3/25/86

Under the business name of Winter Well Drill by (signature) Charles Winter

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.