

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Se</u>		<u>SE</u> 1/4 <u>Sw</u> 1/4 <u>Sw</u> 1/4	<u>32</u>	T <u>28</u> S	R <u>2</u> <u>Q/W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1 1/4 E of Derby</u>					
2 WATER WELL OWNER: <u>Craig Barber</u>					
RR#, St. Address, Box #: <u>7001 S. 49th E</u>					
City, State, ZIP Code: <u>Derby, KS 67037</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>70</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>50</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr <u>3/22/95</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>30</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>10</u> in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Public water supply ☐ 8 Air conditioning ☐ 11 Injection well ☒ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☒ 4 Industrial ☒ 10 Lawn and garden only ☐ 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED:					
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued Clamped ☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded ☐ Blank casing diameter <u>5</u> in. to ft., Dia <u>160</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐ 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 7 Torch cut ☐ 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>50</u> ft. to <u>70</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>25</u> ft. to <u>96</u> ft., From ft. to ft.					
6 GROUT MATERIAL: ☐ 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>25</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
☐ 1 Septic tank ☐ 4 Lateral lines ☒ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 2 Sewer lines ☐ 5 Cess pool ☒ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage					
Direction from well? <u>downslope</u> How many feet? <u>50+</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	clint			
4	19	brn clay			
19	60	gally clay			
60	70	shaly lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/22/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>493</u> This Water Well Record was completed on (mo/day/yr) <u>5/5/95</u> under the business name of <u>Reisner Well Drilling</u> by (signature) <u>Reisner</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4