

1 LOCATION OF WATER WELL: Sedgwick		FRACTION SE 1/4 SE 1/4 SW 1/4		SECTION NUMBER 32		TOWNSHIP NUMBER T 28 S		RANGE NUMBER R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 2206 Curtis Ct. Derby, Kansas									
2 WATER WELL OWNER: SAYRE, Steven		Board of Agriculture, Division of Water Resource							
RR#,ST. ADDRESS,BOX #: 2206 Curtis Ct.		Application Number:							
CITY, STATE: Derby, Kansas		ZIP CODE:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 103 ft. ELEVATION:							
1 Mile N W E S		Depth of groundwater Encountered: ft.							
		WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/17/03							
		Pump test data: Well water was ft. after hours of pumping @ gpm							
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm							
		Bore Hole Diameter 12 in. to 103 ft. and in. to ft.							
WELL WATER TO BE USED AS:		9. Dewatering 11. Injection well							
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)									
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									
Was a chemical/bacteriological sample submitted to Department?		YES NO ; If yes, what mo/day/yr was sample submitted							
Was Water Well Disinfected?		YES NO							
5 TYPE OF CASING USED:		CASING JOINTS: Glued Threaded							
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)		Welded Clamped							
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26									
Blank casing diameter 5 in. to 57 ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface: 24 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214									
TYPE OF SCREEN OR PERFORATION MATERIAL:		11. Other (specify)							
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		11. None (open hole)							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes									
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)									
SCREEN - PERFORATION INTERVAL From 57 ft. to 103 ft., From ft. to ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 24 ft. to 103 ft., From ft. to ft., From ft. to ft.									
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well									
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)									
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? North How many feet? 30									
From To LITHOLOGIC LOG		From To LITHOLOGIC LOG							
0	3	topsoil							
3	28	tan clay							
28	30	fine sand							
30	35	tan shale							
35	37	fine sand							
37	45	tan shale							
45	46	sandstone							
46	55	tan shale							
55	76	gray shale							
76	78	limestone							
78	79	gray shale							
79	82	black shale							
82	102	black shale-gypsum							
102	103	limestone							
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/17/2003 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/20/2003									
under the business name of Harp Well & Pump Service Inc. by (signature) <i>J. d. d. S. Harp</i>									