

LOCATION OF WATER WELL:

FRACTION

SECTION NUMBER

TOWNSHIP NUMBER

RANGE NUMBER

SedgwickNW 1/4 NW 1/4 SW 1/430T 28SR 2E E/W

Distance and direction from nearest town or city street address of well if located within city?

870 Winding LaneDerby, Kansas

WATER WELL OWNER: KLAUSMEYER CONSTRUCTION
RR#,ST. ADDRESS,BOX #: 10008 W. York
CITY, STATE: Wichita, KansasZIP CODE:

Board of Agriculture, Division of Water ResourceApplication Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N
NWNE
SWSE
S
1 Mile
W
E

DEPTH OF COMPLETED WELL: 82 ft.ELEVATION:
Depth of groundwater Encountered: ft.
WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/26/08
Pump test data: Well water was ft. after hours of pumping @ gpm/
Est. Yield: gpmWell water was ft. after hours of pumping @ gpm/
Bore Hole Diameter 12 in.to 82 ft.and in.to ft./
WELL WATER TO BE USED AS:
1. Domestic3. Feedlot5. Public water supply7. Lawn and garden only9. Dewatering11. Injection well
2. Irrigation4. Industrial6. Oil field water supply8. Air conditioning10. Monitoring well12. Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? YESNO; If yes, what mo/day/yr was sample submittedYESNO
Was Water Well Disinfected?YESNO

TYPE OF CASING USED:
1. Steel3. RPM (SR)5. Wrought Iron7. Fiberglass9. Other (Specify below)
2. PVC4. ABS6. Asbestos-Cement8. Concrete tileSDR-26
Blank casing diameter 5 in.to 32 ft., Dia.in.to ft., Dia.in.to ft./
Casing height above land surface: 12 in.,Weight: 2.35 lbs. / ft.Wall thickness or gauge No. .214
TYPE OF SCREEN OR PERFORATION MATERIAL:
1. Steel3. Stainless Steel5. Fiberglass7. PVC9. ABS11. Other (specify)
2. Brass4. Galvanized6. Concrete Tile8. RMP (SR)10. Asbestos-Cement12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1. Continuous slot3. Mill slot5. Gauzed wrapped7. Torch cut9. Drilled holes11. None (open hole)
2. Louvered shutter4. Key punched6. Wire wrapped8. Saw cut10. Other (specify)
SCREEN - PERFORATION INTERVALFrom 32 ft.to 82 ft.,ft.ft.
GRAVEL PACK INTERVALS:From 24 ft.to 82 ft.,ft.ft.

GROUT MATERIALS:1. Neat cement2. Cement Grout3. BentoniteOther bentonite hole plug
Grout Intervals: From 4 ft.to 24 ft.,ft.ft.
What is the nearest source of possible contamination?
1. Septic tank4. Lateral lines7. Pit privy10. Livestock pens13. Insecticide storage15. Oil well/Gas well
2. Sewer lines5. Cess Pool8. Sewage lagoon11. Fuel storage14. Abandon water well16. Other (specify below)
3. Watertight sewer line6. Seepage pit9. Feed yard12. Fertilizer storage
Direction from well? NorthHow many feet? 10 ft. plus

LITHOLOGIC LOGLITHOLOGIC LOG

Contractor's or Landowner's Certification: This water well was 1. constructed2. reconstructedor 3. pluggedunder my jurisdiction and
was completed on (mo/day/year) 11/26/2008and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236This water well record was completed on (mo/day/year) 11/28/2008
under the business name of Harp Well and Pump Serviceby (signature) Todd S. Harp