5501-27R

WATER WELL RECOR	ນ	Form W	WC-5	Di	vision of Wate	r Resources App. N		
1 LOCATION OF WATER WELL: County: Sedgwick		Fraction 1/4 UE	-145W 14	Section	on Number	Township No. T 28 S	Range Number R 2	
			Global Positioning System (GPS) information:					
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Latitude: .37.641.55(in decimal degrees)			
				Longitude: 97.25352 (in decimal degrees)				
Well located within McConnell AFB, Wichita, KS				Elevation:				
					Datum:			
2 WATER WELL OWNER: 22 CEI/CEIER				Collec	Collection Method:			
RR#, Street Address, Box #	30 Pittsburg St. Suite	120	GPS unit (Make/Model: Garmin 60C					
City, State, ZIP Code	nell AFB, KS 67221-3	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey						
City, State, Zir Cour	1011 AFB, NS 0/221-3	Est. Accuracy:						
3 LOCATE WELL				1.				
WITH AN "X" IN 4 D	EPTH OF	COMPLETED WELI	լ 15.0		ft.			
	ION BOX: Depth(s) Groundwater Encountered (1)						(3) ft.	
N WE	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
	Pump test data: Well water wasft. after hours pumping							
TOTAL NATIONAL AND A STATE OF THE STATE OF T							nping gpm	
	Hole Diam	ter 8.25 in. to .16.0 ft., and in. to						
WELL WATER TO BE USED AS: Dublic water supply Geothermal Dis						Injection well		
							Other (Specify below)	
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well								
1						ies V No		
S    mile  W/at		day/yr sample was sub		• • • • • • • • •				
Wat	er well disin	fected? Yes 🔽						
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .2 in. to .5 ft., Diameter .7 in. to .7 ft., Diameter .7 ft.								
Casing height above land surface. Flush in., Weight								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel ✓ PVC □ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot								
Louvered shutter Key punched Sirve wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From16.0 ft. to3.5 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other								
Grout Intervals: From 3.5 ft. to 2.0 ft., From ft. to ft., From ft. ft. ft.								
What is the nearest source of possible contamination:								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
			Fertilizer s		Oil well/g			
Direction from well			Distance	from we	,			
FROM TO	LITHOLOG	IC LOG	FROM	TO	LITHO. L	OG (cont.) <u>or</u> PLI	UGGING INTERVALS	
0  16.0   Clay								
		1						
			<del> </del>					
	<u></u>		+ -				<u> </u>	
7 CONTRACTOR'S OR I A	MDOMAIR	D'S CEDTIEICATIO	N. This	ar mall -	voc 🗖 comet	ruoted 🗆 racaret	ruoted or Daluesed	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was								
Kansas Water Well Contractor's License No710 This Water Well Record was completed on (mo/day/year) .12/27/2014								
Nansas water Well Contractor	Solow Grou	no Inis i	water well b	cecora W	vas complete	u on (mo/day/year	() .:#(#.V(#X!#	
under the business name of .Below Ground Surface. Inc. by (signature)								
(white, blue, pink) to Kansas Depar to								
Telephone 785-296-5524. Send one								
http://www.kdheks.gov/waterwell/inde								
KSA 82a-1212				C	heck: 🔲 W	hite Copy, 🔲 B	lue Copy, 🔲 Pink Copy	