ST 17- MW17

WATER WELL REC	CORD	Form W	WC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL: County: Sedgwick		Fraction 1/4 1/4 SE	1/4 NW 1/4	Section Number Township No. Range Number	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:					
from nearest town or intersection: If at owner's address, check here .				Latitude: .37.62934 (in decimal degrees)	
Well located within	Wichita, KS		Longitude: 97.25530 (in decimal degrees)		
				Elevation:	
2 WATER WELL OWNER: 22 CEI/CEIER			☐ Datum: ☑ WGS 84, ☐ NAD 83, ☐ NAD 27		
RR#, Street Address,	CEIER 30 Pittsburg St, Suite	. 120	Collection Method: ☐ GPS unit (Make/Model: Garmin 60C)		
0', 0', 770 0 1				Digital Map/Photo, Topographic Map, Land Survey	
ony, state, En cour	· McConr	nell AFB, KS 67221-	3017	Est. Accuracy:	
3 LOCATE WELL					
WITH AN "X" IN					
SECTION BOX:	Depth(s) Ground	lwater Encountered	(1)	ft. (2) ft. (3) ft.	
, N	WELL SSTATIC WATER LEVEL				
	Pump test data: Well water was				
925					
W E Bore Hole Diameter 9.49					
Demostic Decodlet Delifield water quanty Devetoring Defect (Specific below)					
SWSE Domestic Feediot On held water supply Dewatering Other (specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes V No					
S If yes, mo/day/yr sample was submitted					
Water well disinfected? ☐ Yes ✓ No					
5 TYPE OF CASING USED: Steel V PVC Other					
CASING JOINTS: Glued Clamped Welded 7 Threaded					
Casing diameter .2 in. to .10.0 ft., Diameter in. to ft., Diameter ft.					
Casing height above land surface. Flush in., Weight					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20.0 ft. to 10.0 ft., From ft. to ft.					
From					
GRAVEL PACK INTERVALS: From .21.0 ft. to .7.9 ft., From . ft. ft.					
From					
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other Grout Intervals: From 7.9 ft. to 5.9 ft., From 9.8 ft. to 1.6 ft., From ft. to ft.					
What is the nearest source			*	The to	
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
□ Watertight sewer lines □ Seepage pit □ Feedyard □ Fertilizer storage □ Oil well/gas well □ Direction from well □ Distance from well					
FROM TO	LITHOLOG		FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0 21.0 Clay	LITTOLOG	ic Log	TROM	TO ETTIO. LOG (COIIL.) OF PLOGGING INTERVALS	
Clay					
			-		
			<u> </u>		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\bigz \) constructed, \(\precip \) reconstructed, or \(\precip \) plugged					
under my jurisdiction and was completed on (mo/day/year) .04/06/2015 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No7.10					
under the business name of Below Ground Surface, Inc. by (signature)					
INSTRUCTIONS: Use ty new	vriter or ball point pen	PLEASE PRESS FIRML	Y and PRINT o	early. Please fill in blanks and check the correct answers. Send three copies	
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					