OT 547 - MW26

WATER WELL RECORD	Form WWC-5	Division of Water Resources App. 1	No.	
1 LOCATION OF WATER WE			Range Number	
County: Sedgwick	1/4 1/4 SW 1/4 SE			
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:				
from nearest town or intersection: If at owner's address, check here . Latitude: .37,637,60			(in decimal degrees)	
Well located within McConnell AFB, Wichita, KS			Longitude: 97.25072 (in decimal degrees)	
		Elevation:		
2 WATER WELL OWNER: 22 CEI/CEIER			Collection Method:	
RR#, Street Address, Box #: 15657830 Pittsburg St. Suite 120		GPS unit (Make/Model: Garmin 60C		
City, State, ZIP Code : McConnell AFB, KS 67221-3617		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
,	VICCOTTIEN AT B. NO 07221-0017	Est. Accuracy: <3 m, 3-5 m,] 5-15 m,	
3 LOCATE WELL 25 0				
	TH OF COMPLETED WELL 25.0		(2)	
SECTION BOX: Depth(s)	Groundwater Encountered (1)	ft. (2) ft.	(3)π. /4/ 03/31/15	
WELL'S	N WELL'S STATIC WATER LEVEL. Drv			
	EST VIELD - com Well wester was " A offer " hours numning " gpm			
[NW]NE] D				
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well				
Demostic Decellet Doil field water supply Dewatering Dother (Specify below)				
SW SE Domestic Preedict Domestic-lawn & garden Monitoring well				
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No				
S If yes, mo/day/yr sample was submitted				
1 mile Water well disinfected? ☐ Yes ☑ No				
5 TYPE OF CASING USED: Steel V PVC Other				
CASING JOINTS: Glued Clamped Welded Threaded				
Casing diameter .2 in. to .15.0 ft., Diameter .7 ft., Diameter .7 ft.				
Casing height above land surface. Flush in., Weight				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
☐ Steel ☐ Stainless Steel				
Brass Galvanized Steel None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
Continuous slot ✓ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)				
From				
GRAVEL PACK INTERVALS: From . 26.0 ft. to . 12.0 ft., From ft. to ft.				
From				
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other				
Grout Intervals: From 12.0 ft. to 10.0 ft., From 10.0 ft. to 1.7 ft., From ft. to ft. to ft.				
What is the nearest source of possible contamination:				
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)				
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well				
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well Distance from well				
	HOLOGIC LOG FROM	The state of the s		
·	HOLOGIC LOG PROM	10 ETTHO. LOG (cont.) or FI	COOING INTERVALS	
0 26.0 Clay				
			· · · · · · · · · · · · · · · · · · ·	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged				
under my jurisdiction and was completed on (mo/day/year) .03/31/20.15 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No7.10 This Water Well Record was completed on (mo/day/year) .04/18/2015				
under the business name of Below Ground Surface, Inc. by (signature)				
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check de correct answers. Send three copies				
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at				
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy				