	WATER W	ELL R	ECO	RD F	orm W	/WC-5	KSA 82	a-1212	2					
1 LOCATION OF WATER WELL:	FRACTION					CTION NUME	BER TO				RANGE NUMBER			
Sedgwick	SW 1/4		1/4	SW	1/4	31	T	28	S	R	2E	E/W		
Distance and direction from nearest town or city					of Duo	mauter I in	o of 000	E Ma	a darrilari	Dowby	. Var	2000		
1238.96' West of Triplecree	K COMPAN			C, ZZ' E.	. 01 Pro	perty Lin	ie 01 900	L. Me	adowiark	Derby	, Kai	1525		
	BE. Lewis	1123, 11	ıc.						Board of Ag	riculture, Divisio	n of Wat	er Resource		
,	hita, Kansas					ZIP CODE:			Application Nu	mber:				
<u></u>	DEPTH OF COM	PLETED \	WELL:	8	5 1	t.	ELEVAT	ION:						
WITH AN "X" IN SECTION BOX:	epth of groundwate					ft.			ft.			ft.		
1	ELL'S STATIC W			32	FT. BE	LOW LAND	SURFACE I	MEASUF	RED ON mo	/day/yr:	6/25/1	15		
NW	Pı	ımp test d	lata:	Well wa	ter was		ft. a	fter	hour	rs of pumping	@	gpm		
	Est. Yield:	gpm		Well wa	iter was		ft. a	fter	houi	rs of pumping	@	gpm		
	Bore Hole Diamete	•		n.	to	85	ft. a	nd	in.		to	ft.		
	'ELL WATER TO I	BE USED 5. Feedlot		Dublic w	tor eunn	y Z Law	n and garde	en only	9. Dewater	9	•	on well		
		. Industri		Oil field v			onditioning		10. Monito r		er (Spe	cify below)		
	Was a chemical/bact				•			\odot	; If yes,	what mo/day	/yr wa	s sample		
sı	ubmitted					Wa	s Water We	Il Disinfe	cted?	(YES)	NC)		
TYPE OF CASING USED: 1. Steel 3. RPM (S	5. Wrough	t Iron	7. 1	Fiberglass	9.	Other (Spec	cify below)	CASI	NG JOINTS:		T	hreaded		
1. Steel 3. RPM (S	6. Asbesto	s-Cemen	t 8. (Concrete t	tile S	DR-26				Welded	(Clamped		
Blank casing diameter 5	in. to		t.,	Dia.	in.	to	ft.,	n	ia.	in. to		ft.		
	12 in.,	-15	•		2.35	lbs. / ft.	·					16.		
Casing height above land surface: TYPE OF SCREEN OR PERFORATION	,		VV	/eight:	2.33	IDS. / II.		wan mic	kness or gau	ige No	214			
1. Steel 3. Stainless Steel	5. Fiberglass	6	7. P	vc	9	. ABS		11. Oth	er (specify)					
2. Brass 4. Galvanized	6. Concrete	Tile	8. F	MP (SR)	10	. Asbestos-C	Cement	12. Non	e used (oper	n hole)				
SCREEN OR PERFORATION OPENIN	GS ARE:													
1. Continuous slot 3. Mill s	lot 5.	Gauzed v	wrappe	d	7.	Torch cut		9. Drille	d holes	11. N oi	ne (ope	en hole)		
2. Louvered shutter 4. Key p	ounched 6.	Wire wra	pped		8.	Saw cut	1	0. Other	(specify)					
SCREEN - PERFORATION INTERVAL	From	45	ft.	to	85	ft.,	From		4	4.		4		
SOREEN - LEKT SKATION INTERVAL	From	45	ft.	to		ft.,	From		ft.	to		ft.		
GRAVEL PACK INTERVALS:	From	24	ft.	t		ft.,	From		ft. ft.	to		ft.		
S, V, V ZE I , V SI C II V ZI C , V ZE S.	From		ft.	t		ft.,	From			to.		ft.		
6 GROUT MATERIALS: 1 Neat									ft. Other hen	to		ft.		
Grout Intervals: From 4	ft. to		ment G	From		3. Benton ft. to				tonite hole				
What is the nearest source of possible c	ontamination:		·)	ft.,	From		to	ft.		
1. Septic tank 4. Lateral lines 7. Pit privy 1						ock pens	13.	13. Insecticide storage			15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon					11. Fuel s	1. Fuel storage			14. Abandon water well			16. Other (specify below) None Apparent		
3. Watertight sewer line 6. Seepa	age pit	9. Feed ya	ard		12. Fertili	zer storage				None	Арр	arent		
Direction from well?	LITUOLOGI	0100			T =	. 1 +	<u> </u>	low mar		20101.04				
From To	LITHOLOGI	C LOG	<u> </u>		Fron	n To			LITHOL	OGIC LO	<u>خ</u>			
0 3 topsoil 3 35 clay					+									
35 50 medium sand	đ													
50 80 grey shale														
80 85 limestone					_		_							

					 		+							
7 Contractor's or Landowner's Certif	ication: This wate	r well was	1.00	onstructe	d) 2.	reconstruc	ted or	3. p	lugged	under my jur	isdiction	n and		
was completed on (mo/day/year)	6/25/2015		_			the best of n			elief.					
Kansas Water Well Contractor's Licer						was comple	-			6/2015				
		C-				•	5.1 (1110/1							
under the business name of Harp	wen and Pu	mp Ser	vice		uy	(signature)	<u> </u>	10	raa S	5. Ha	<u>rp</u>			