WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SW 1/4 Sedgwick NWSE 1/4 31 Т 28 S R **2E** E/W Distance and direction from nearest town or city street address of well if located within city? 1300 E. Lookout St. Derby, Kansas SHARP HOMES WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 430 Walnut Wichita, Kansas CITY, STATE: ZIP CODE Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 70 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** Depth of groundwater Encountered: ft. ft. ft. 30 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ NW NE gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Ī Bore Hole Diameter 12 ft. in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only -SF .SW 3. Feedlot 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation (NO) ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (YES) submitted Was Water Well Disinfected? NO TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: C Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC Blank casing diameter 5 45 ft. Dia. in. to in. to ft.. Dia. ft. in. to 12 2.35 Casing height above land surface: in. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 8. RMP (SR) 12. None used (open hole) 2. Brass 6. Concrete Tile 4. Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 7. Torch cut 9. Drilled holes 1 Continuous slot 5. Gauzed wrapped 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 70 From to ft., From to ft. ft. to From ft., From to ft. 24 ft GRAVEL PACK INTERVALS: to 70 From ft.. From ft. to ft. From to ft.. From ft. ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft., From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line South How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Tο From Τo topsoil 3 18 clay 18 60 medium sand 60 65 grey shale 65 70 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 9/17/2015 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/18/2015 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb