■ Original Record □ Correction □ Change in Well Use Resources App. No.	Well ID
	ship Number   Range Number
County: Sedgwick 1/4 1/4 SW 1/4 SE 1/4 6 T	28 S R 2 ■ E □ W
2 WELL OWNER: Last Name: First: Street or Rural Address where well	is located (if unknown, distance and
Business: 22 CEI/CEIER direction from nearest town or intersection): If at owner's address, check here:	
Address: 15657830 Pittsburg St., Suite 120 Address: Well located within McConnell AFB, Wichita, KS	
	FB, Wichita, KS
City: McConnes AFB State: KS ZIP: 67221-3617	
3 LOCATE WELL 4 DEPTH OF COMPLETED WELL:25.3 ft. 5 Latitude:	37.63545 (decimal degrees)
Doubles Croundwater Engagement 1)	
2) A 2) A or 4) $\square$ Dry Well 1 vv .	decimal degrees)
	■ WGS 84 □ NAD 83 □ NAD 27
Source for Buttude	c/Longitude:
and the state of t	ke/model: Garmin 60c
	enabled? ■ Yes □ No)
1   1   1   2   2   2   2   2   2   2	☐ Topographic Map
Well water was ft.	r:
after hours pumping	
Estimated Yield:gpm 6 Elevation:	ft. Ground Level TOC
	urvey GPS Topographic Map
mile  Dote Note Districts	,
7 WELL WATER TO BE USED AS:	
	r Sunnive Jacca
	r Supply: lease
	cased  Geotechnical
	many bores?
	☐ Horizontal ☐ Vertical
3. ☐ Feedlot ☐ Air Sparge ☐ Soil Vapor Extraction ☐ Dop ☐	Surface Discharge  Inj. of Water
	:
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:	
Water well disinfected? ☐ Yes ■ No	
8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other	
Casing diameter	
Casing height above land surface0.2 in. Weight	ge No. Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL:	
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)	***************************************
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
☐ Continuous Slot ■ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)	
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)	
SCREEN-PERFORATED INTERVALS: From 25.0 ft to 15.0 ft From - ft to -	From - ft to - ft
GRAVEL PACK INTERVALS: From 26.0 ft. to 11.8 ft., From ft. to ft.	From - ft to - ft
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other	., 11011
Grout Intervals: From 11.8 ft. to 9.0 ft., From 9.0 ft. to 2.6 ft., From	Φ +
Nearest source of possible contamination:	п. ю п.
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens	□ Ingasticida Starona
Sewer Lines □ Cess Pool □ Sewage Lagoon ■ Fuel Storage	☐ Insecticide Storage ☐ Abandoned Water Well
Watertight Sewer Lines   Seepage Pit   Feedyard   Fertilizer Storage	Oil Well/Gas Well
Other (Specify)	LI OII WOII/Oas WOII
Direction from well? Distance from well?	ft
10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG	G (cont.) or PLUGGING INTERVALS
0 26.0 Clay	G (COIL.) OF I LOGOTING INTERVALS
20.0 010	
Notes:	
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged	
under my jurisdiction and was completed on (mo-day-year) 12/14/2015 and this record is true to the best of my knowledge and belief	
Kansas Water Well Contractor's License No(10 This Water Well Record was completed on (mo-day-year) 2/1/2016	
under the business name of Below Ground Surface, Inc.	
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,	
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.	
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your rec	cords. Telephone 785-296-5524.