			WATER	R WELL	RECC	RD F	orm W\	VC-5 K	(SA 82a-12	212		
111	OF WATER	WELL:	FRACTION				SEC	TION NUMBE		HIP NUMBER		NUMBER
Sedgy			NW	1/4 S			1/4	30	T	28 S	R 2	E E/W
i .		nearest town or city		of well if loca rby, Kai		city?						
	R WELL O		USMEY			ICTION						
_	ADDRESS,		08 W. Yor		1101111					Board of Ag	griculture, Division of	Water Resource
,	CITY, S	****	hita, Kans	_			Z	IP CODE: 6	57215	Application Nu	umber:	
	WELL'S LO	CATION 4	DEPTH OF C	OMPLETE	D WELL:	85	ft.		ELEVATION	:		
WITH A	N "X" IN SEC	TION BOX: De	epth of ground	water Ence	ountered:		f	t.		ft.		ft.
		- W	ELL'S STATI	C WATER	LEVEL	35	FT. BELO	W LAND S	URFACE MEA	SURED ON mo	o/day/yr: 1/1	10/19
1   2-	NW	-NE		Pump te	st data:	Well water	er was		ft. after	hou	rs of pumping @	gpm
w Mile	1	'	Est. Yield:	٤	gpm	Well wat			ft. after		rs of pumping @	gpm
<b>&gt;</b> w			Bore Hole Dia			in.	to	85 f	t, and	in.	to	ft.
\—	sw	J	/ELL WATER 1. Domestic	3. Feed	SED AS: S <b>ilot</b> 5	. Public wat	er supply	7. Lawn	and garden o	9. Dewate	g	jection well Specify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well												
' -	s		Was a chemical	/bacteriologi				YES	NO		, what mo/day/yr	was sample NO
			ubmitted			·			Water Well Dis		YES	
	PE OF CAS . Steel	NG USED: 3. RPM (S	5. Wr	ought Iron	7	Fiberglass		Other (Specif	fy below) C	ASING JOINTS:	Welded	Threaded Clamped
l	PVC	4. ABS	•	estos-Cer	ment 8	. Concrete til	le SI	R-26			Weided	Clamped
	ing diamete	_	in. t	o <b>50</b>	ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing he	eight above	land surface:	12	in.,	,	Weight:	2.35	lbs. / ft.	Wall	thickness or ga	uge No21	4
1	•	R PERFORATIO									•	-
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)												
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
SCREEN	OR PERFO	RATION OPENIN	IGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole)												( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)												
SCREEN -	PERFORA	TION INTERVAL	From	5	<b>50</b> ft.	to	85	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.
G	RAVEL PAG	CK INTERVALS:	From	2	<b>24</b> ft.	to	85	ft.,	From	ft, ´	to	ft.
			From		ft.	to	•	ft.,	From	ft.	to	ft.
6 GROU	JT MATERI	ALS: 1. Near	t cement	2	Cement	Grout		3. Bentonii	te	Other bei	ntonite hole p	olug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to												
What is the nearest source of possible contamination:								13 Inse	cticide storage	e 15. Oil wel	I/Gas well	
1. Septic tank 4. Lateral lines 9. Source losson 11. Final storage 14. Abandon water well 16. Other (specify												
2. Sewe		5. Cess			ed yard			er storage	14. Aua	nuon water we	· · ·	
	rtight sewe from well?	r line 6. Seep East	age pit	9. гес	au yaru	'	iz. Feruiiz	er storage	How	many feet? 40	) ft. plus	
From	To		LITHOL	OGIC L	OG		From	То	T		OGIC LOG	
0	3	topsoil										
3	48	clay					ļ	<u> </u>				
48	59	fine sand					-	+	+			
59	85_	gray shale							<del>                                     </del>			
							<del> </del>		<del> </del>			
				<u> </u>				-				
							+	-				
7 0	troot	l andowers of Co. 1	ification: TL:	t-=		aanstruist-	<del>-</del> -	reconstruct	ed or 3.	plugged	under my jurise	diction and
E contacto of Editorior Contactor and Incompany												
was completed on (mo/day/year) 1/10/19 and this record is true to the best of my knowledge and belief.												
Kansas	Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/14/19											
under the business name of Harp Well and Pump Service by (signature)  Todd S. Horb												Ъ