WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER LOCATION OF WATER WELL: FRACTION NWSedgwick 30 28 1/4 1/4 2E E/W Distance and direction from nearest town or city street address of well if located within city? 3413 N. Tyndall Derby, Kansas WATER WELL OWNER: KLAUSMEYER CONSTRUCTION Board of Agriculture, Division of Water Resource 10008 W. York RR#,ST. ADDRESS,BOX #: CITY, STATE Wichita, Kansas ZIP CODE: Application Number: 86 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 16 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ apm NE Est. Yield: Well water was ft. after hours of pumping @ gpm ≌ Bore Hole Diameter 12 to 86 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? submitted (YES) Was Water Well Disinfected? NO 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 in. to 45 ft.. Dia. ft.. in to Dia. in ft to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass 8. RMP (SR) Concrete Tile 12. None used (open hole) 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 9. Drilled holes 11. None (open hole) 7. Torch cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 From to 86 ft From ft. From ft. to ft., From ft. GRAVEL PACK INTERVALS: 24 86 From ft... From ft ft. From ft. to ft., From ft. to ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2 Cement Grout 3. Bentonite Grout Intervals: From ft. to ft., From 53 ft. From ft. to What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North Direction from well? How many feet? 10 ft. plus From. Τо LITHOLOGIC LOG From To LITHOLOGIC LOG O tonsoil 3 29 <u>clay</u> 29 <u>42</u> fine sand 42 53 medium sand 53 86 grey shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed plugged under my jurisdiction and

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/27/2020 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/4/2020

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp