

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE 1/4 SW 1/4 SW 1/4	1	T 28S S	R 2 EW
Distance and direction from nearest town or city street address of well if located within city? 143rd E - 31 S - 1/4 E - North Side					
2 WATER WELL OWNER: McCullum Construction					
RR#, St. Address, Box #: 407 State St.				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: Augusta, KS				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 46 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 9/27/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 45 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well ☐ 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: ☒ Glued ☐ Clamped			
☐ 1 Steel ☐ 3 RMP (SR) ☒ 2 PVC ☐ 4 ABS		☐ 5 Wrought iron ☐ 8 Concrete tile ☐ 6 Asbestos-Cement ☐ 9 Other (specify below)			
Blank casing diameter 5 in. to ft., Dia		in. to ft., Dia			
Casing height above land surface +12 in., weight 160 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		☒ 7 PVC ☐ 10 Asbestos-cement ☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐ 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐ 1 Continuous slot ☒ 3 Mill slot ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 7 Torch cut ☐ 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 40 ft. to 60 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From 20 ft. to 60 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		☐ 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other			
Grout intervals: From 3 ft. to 20 ft., From ft. to ft.					
What is the nearest source of possible contamination:		☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage			
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 2 Sewer lines ☐ 5 Cess pool ☒ 8 Sewage lagoon ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard		How many feet? 64+			
Direction from well? DOWN SLOPE (E)					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Earth			
5	10	Brown clay			
10	40	Yellow clay			
40	60	Shaley Sand			
RECEIVED AUG 31 1990 DIVISION OF ENVIRONMENT					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/27/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) 9/27/89 under the business name of Reisner Well Drilling by (signature) <i>Jerry Reisner</i>					