

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW ¼ NE ¼ NE ¼	Section Number 6	Township Number T 28 S	Range Number R 2 EW
Distance and direction from nearest town or city street address of well if located within city? 2,780' SSW from the intersection of Pawnee Avenue and Rock Road, Wichita, KS MW-4A 52895010					
2 WATER WELL OWNER: Boeing Military Airplanes RR#, St. Address, Box # : P. O. Box 7730, M/S K06-00 Board of Agriculture, Division of Water Resources City, State, ZIP Code : Wichita, KS 67277-7730 Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION: Approx. Surface Elev: 1379.6 Depth(s) Groundwater Encountered 1. 20.5 ft. 2. . ft. 3. . ft. WELL'S STATIC WATER LEVEL: 2.7 ft. below land surface measured on mo/day/yr 04/27/89 Pump test data: Well water was . ft. after . hours pumping . gpm Est. Yield N/A gpm: Well water was . ft. after . hours pumping . gpm Bore Hole Diameter . 9 in. to 43 ft., and . in. to . ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes (No)			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . Clamped . 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . Blank casing diameter . 2 in. to 20 ft., Dia . in. to . ft., Dia . in. to . ft. Casing height above land surface . -3 in., weight . lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) . SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 20 ft. to 43 ft., From . ft. to . ft. GRAVEL PACK INTERVALS: From 20 ft. to 43 ft., From . ft. to . ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other . Grout Intervals: From 0 ft. to 17.5 ft., From 17.5 ft. to 20 ft., From . ft. to . ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Aircraft Plant Direction from well? E How many feet? 180					
		LITHOLOGIC LOG		PLUGGING INTERVALS	
FROM	TO			FROM	TO
0	8	Dark Gray-Brown Fat Clay			
8	14	Red-Brown Fat to Lean Clay, Trace Sand			
14	20.5	Olive-Gray Fat Clay With Calcareous Material			
20.5	43	Olive-Gray Highly Weathered Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/19/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 5-27-89 under the business name of Terracon Consultants, Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answer. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					