


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 SW 1/4 Section Number 4 Township Number T 23 S Range Number R 2 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: McConnell AFB
 RR#, St. Address, Box # :
 City, State, ZIP Code: Wichita, Kansas

Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 29.0 ft. ELEVATION: 1345
 Depth(s) Groundwater Encountered 1. 2.0 ft. 2. 2.0 ft. 3. 2.0 ft.
 WELL'S STATIC WATER LEVEL 6.34 ft. below land surface measured on mo/day/yr 11/28/88
 Pump test data: Well water was None ft. after 11/28/88 hours pumping 11/28/88 gpm
 Est. Yield 11/28/88 gpm: Well water was None ft. after 11/28/88 hours pumping 11/28/88 gpm
 Bore Hole Diameter 11/28/88 in. to 11/28/88 ft., and 11/28/88 in. to 11/28/88 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted 11/28/88
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 2 in. to 8.0 ft., Dia. 8.0 in. to 8.0 ft., Dia. 8.0 in. to 8.0 ft.
 Casing height above land surface 0.3 in., weight 8.0 lbs./ft. Wall thickness or gauge No. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 8.0 ft. to 27.0 ft., From 8.0 ft. to 27.0 ft.
 GRAVEL PACK INTERVALS: From 8.0 ft. to 29.0 ft., From 8.0 ft. to 29.0 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement/Bentonite
 Grout Intervals: From 1.0 ft. to 2.0 ft., From 2.0 ft. to 2.0 ft., From 2.0 ft. to 2.0 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage unknown

Direction from well?		LITHOLOGIC LOG		PLUGGING INTERVALS	
FROM	TO			FROM	TO
0	2.0	Fill - Wh Rock			
2.0	4.0	Soil - DK Br			
4.0	16.5	Clay - DK Br Si Damp			
16.5	22.5	" - Br Str			
22.5	26.0	" - Gr Br to Rd Damp			
26.0	26.5	Sandstone - Red			
26.5	29.0	Clay - Gray Dry			

RECEIVED RECEIVED

JUN 15 1989

OCT 27 1989

DIVISION OF ENVIRONMENT DIVISION OF ENVIRONMENT

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/28/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 494 This Water Well Record was completed on (mo/day/yr) 11/28/88 under the business name of Southwestern Lab by (signature) Robert J. Daniel